

ZTZ



Toroidal LPG tanks for multi-valve joined with external fitting nozzle.

APPLICATION

Tanks are intended for LPG mixture storage in gas installations in motor vehicles.

TECHNICAL DATA

- manufacture – class I
- test pressure 3,00 MPa,
- bursting pressure min. 6,75 MPa,
- manufactured according to UN ECE 67 R-01

CERTIFICATES

Homologation

Type of tank	Diameter D [mm]	Height H [mm]	Capacity [l]	Allowable filling 80% [l]	Mass Q [kg]
ZTZ 566/180	566	180	33,0	26,4	22,30
ZTZ 580/200	580	200	39,0	31,2	24,10
ZTZ 580/220	580	220	43,50	34,8	26,20
ZTZ 580/250	580	250	50,00	40,0	28,10
ZTZ 600/200	600	200	41,50	33,2	25,70
ZTZ 600/220	600	220	45,00	36,0	27,00
ZTZ 600/250	600	250	54,00	43,2	28,50
ZTZ 600/270	600	270	59,00	47,2	31,00
ZTZ 630/200	630	200	45,00	36,0	27,10
ZTZ 630/220	630	220	51,00	40,8	28,00
ZTZ 630/250	630	250	59,00	47,2	29,80
ZTZ 630/270	630	270	64,00	51,2	32,00
ZTZ 650/200	650	200	50,00	40,0	25,00
ZTZ 650/220	650	220	56,00	44,8	26,40
ZTZ 650/250	650	250	65,00	52,0	32,20
ZTZ 650/270	650	270	70,00	56,0	34,30