

ZTP

Full toroidal LPG tanks for multi-valve joined with external fitting nozzle.



APPLICATION

Tanks are intended for LPG mixture storage in gas installations in motor vehicles.

TECHNICAL DATA

- manufacture – class I
- test pressure 3,00 MPa,
- bursting pressure min. 6,75 MPa,
- manufactured according to UN ECE 67 R-01

CERTIFICATES

Homologation

Type of tank	Diameter D [mm]	Height H [mm]	Capacity V [l]	Allowable filling 80% [l]	Mass Q [kg]
ZTP 580/200	580	200	41,5	33,2	25,80
ZTP 580/220	580	220	46,5	37,2	27,70
ZTP 580/250	580	250	54	43,2	28,70
ZTP 600/200	600	200	45,5	36,4	27,00
ZTP 600/220	600	220	51,0	40,8	28,50
ZTP 600/250	600	250	59,0	47,2	30,50
ZTP 600/270	600	270	65,0	52,0	32,00
ZTP 630/200	630	200	49,0	39,2	28,60
ZTP 630/220	630	220	55,0	44,0	30,00
ZTP 630/250	630	250	64,0	51,2	32,00
ZTP 630/270	630	270	71,0	56,8	34,00
ZTP 650/200	650	200	54,0	43,2	30,00
ZTP 650/220	650	220	61,0	48,8	32,60
ZTP 650/250	650	250	71,0	56,8	34,20
ZTP 650/270	650	270	77,0	61,6	36,30
ZTP 720/250	720	250	84,0	67,2	37,50
ZTP 720/270	720	270	92,0	73,6	40,50
ZTP 720/300	720	300	103,0	82,4	43,50